STATE ENGINEER OFFICE WELL RECORD

Section 1. GENERAL INFORMATION

(A) Owner of well NASA White Sands Test Facility Street or Post Office Address P.O. Box 20 Owner's We										
	or Post Office Addi and State Las Cruc		0				_			
-										
Well was dri	lled under permit No	No permit - m	nonitoring we	<u>:11 </u>	and is located in the	he:				
						20S R	_			
b. 7	Γract No.	of Map No.			of the	÷				
c. 1	Lot No.	of Block No.		of the						
									zone in Grant.	
(B) Drillin	g Contractor Stev	vart Brothers Drill	ing Company	·	License No.	WD 331				
Address	P.O. Box 2067, 306	Airport Rd., Mila	ап, NM 8702	21						
Drilling Bega	n 06/09/99	Com	npleted 08	/18/99	Type tools Ro	otary Size o	of hole	4 1/4	in.	
Elevation of land surface or at well is Approx. 4870 ft. Total depth of well 695 ft.										
Completion v	vell is 🔀 sha	ıllow 🔲 ar	tesian.		Depth	to water upon complet	ion of	well <u>A</u> j	pprox. 251 ft.	
		Sec	tion 2. PRIN	CIPAL WAT	ΓER-BEARING S	TRATA				
Depth in Feet		Thickness in Feet		Description o	escription of Water-Bearing Formation			Estimated Yield (gallons per minute)		
From To 251 695 444			Andesite					Unknown		
	. 									
- · · · · · · · · · · · · · · · · · · ·									·	
-	<u> </u>	1								
			Sectio	n 3. RECOR	D OF CASING					
Diameter (inches)	Pounds per foot	Threads per in.	Depth i	n Feet Bottom	Length (feet)	Type of Shoe			Perforations From To	
4.5			0	170	170	None			Surface casing	
1.5			0	0 695		None Well		Well casing		
		Section	on 4. RECOF	RD OF MUD	DING AND CEN	MENTING				
Depth in Feet		Hole Diameter	Sacks	Sacks Cubic Feet of Mud of Cement			Method of Placement			
From	To	0.555								
0	170	8.625"				50 Pressure gro		nt from inside of surface casing		

Section 5. PLUGGING RECORD

<u>.</u>			
		-	
<u> </u>			
]	
<u></u>			
	- "		
		<u> </u>	
		Section 7. RE	MARKS AND ADDITIONAL INFORMATION
Well is constructed measurement and pt 545', and 660' - 680	umping ports are lo	VC Westbay Multi-P cated on the Westbay	ort System® casing. Westbay packers are inflated inside the 4 ¼" borehole. Specialized ® well within sampling zones. Westbay® sampling zones are located 345' - 360', 525' -
The undersigned he described hole.	ereby certifies that,	to the best of his kno	wledge and belief, the foregoing is a true and correct record of the above
			Driller
INSTRUCTIONS: of the State Engine	This form should ber. All sections, ex	be executed in triplicates to Section 5, shall	ate, preferably typewritten, and submitted to the appropriate district office be answered as completely and accurately as possible when any well is

of the State Engineer. An sections, except section 3, shall be answered as completely and accurately as possible when any well drilled, repaired or deepened. When this form is used as a plugging record, only Section 1(a) and Section 5 need be completed.